



PORTABLE DRONE CONTROL - MR33

# UAV DEFENSE EQUIPMENT

QUICKLY FORCE THE DRONE TO LAND, HOVER,  
OR RETURN





**TIFA**

Battery capacity Voltage

81.275V



驱赶 迫降

Designed by LeibusSecurity in Shenzhen

无人机便携式管制设备

型号: MR33

输入: DC28V 2A

管制力: 3000

执行标准:

充电

# SIMPLE OPERATION

OPERATION IS SIMPLE TO USE, A LOOK WILL BE USED

WARNING, CUT OFF ALL SIGNAL CONTACT BETWEEN THE DRONE AND THE CONTROLLER, THE DRONE REMOTE CONTROL FAILED, THE VIDEO, THE PICTURE LOST CONTACT, FORCING THE DRONE TO RETURN.

INDEPENDENT RESEARCH AND DEVELOPMENT, PRODUCTION, REASONABLE PRICE, SUFFICIENT POWER

QUICKLY FORCE THE DRONE TO LAND, HOVER, OR RETURN.

PORTABLE DESIGN FOR EASY CARRYING





# DRONE DEFENSE



INTERFERENCE SHIELDING FOR ALL SATELLITE  
POSITIONING SIGNALS INTERFERENCE SHIELDINGFOR ALL SATELLITE POSITIONING SIGNALS

PRODUCT NAME	PORTABLE DRONE CONTROL EQUIPMENT
PRODUCT MODEL	MR33
MAIN ENGINE SIZE	IT IS 101CM LONG, 35CM WIDE AND 16.5CM THICK
POWER SUPPLY	THE BATTERY IS NOT REMOVABLE. BUILT-IN LITHIUM BATTERY :27V/4000MAH
ENDURANCE	CONTINUOUS OPERATION UP TO 2 HOURS, EXTERNAL CHARGER.
MODE OF OPERATION	ONE OR TWO HAND OPERATION, CAN OPEN ANY THREE FREQUENCY BANDS.
HEAT DISSIPATION MODE	AIR COOLING
INTERCEPTION MODE	FORCED RETURN, EVICTION, FORCED LANDING, HOVERING FORCED LANDING, MAP TRANSMISSION INTERFERENCE
INTERCEPT CHANNEL	THREE CHANNELS
FREQUENCY ALLOCATION	3 FREQUENCY 3 CHANNEL
SWITCH	THREE
ANTENNA	BUILT-IN
CONTROL DISTANCE	OPEN LAND> 3000 M
WEIGHT	APPROX. 3KG (BARE)

## RESTRICTED AREA DRONE LOW ALTITUDE CONTROL



WITH THE WIDE APPLICATION AND POPULARITY OF CIVIL AERIAL PHOTOGRAPHY DRONES, MANY AIRPORTS, OIL DEPOTS, POWER STATIONS, BORDER GUARDS, MILITARY RESTRICTED AREAS, ETC., HAVE BEEN REPEATEDLY INTERFERED WITH BY DRONES, AND THE REASONABLE USE OF DRONES IS REQUIRED FOR LOW-ALTITUDE CONTROL OF DRONES IN RESTRICTED AREAS. INDEPENDENT RESEARCH AND DEVELOPMENT, PRODUCTION OF UAV JAMMER, THE EQUIPMENT CAN BE USED FOR THE UAV COMMONLY USED 900M\2.4G AND 5.8G FREQUENCY BANDS FOR INTERFERENCE SHIELDING, FORCING THE UAV REMOTE CONTROL, MAP TRANSMISSION POSITIONING, SIGNAL INTERRUPTION, TO ACHIEVE THE CRASH LANDING/RETURN/HOVER FUNCTION, INTERFERENCE DISTANCE INTERFERENCE DISTANCE, OPEN LAND GREATER THAN 3000-4000 METERS.



SUITABLE FOR OUTDOOR LARGE AREA SIGNAL SHIELDING

# VERY LARGE TRANSMITTING POWER

THE COMPANY INDEPENDENTLY DEVELOPS AND PRODUCES UAV JAMMERS  
THE DEVICE CAN BLOCK INTERFERENCE AGAINST ALL SATELLITE POSITIONING SIGNALS







WIRELESS MORE PORTABLE



STRONG WIRELESS ENDURANCE



UNLIMITED VOLTAGE

SWITCHING CHANNEL	FREQUENCY BAND	INSTRUCTIONS
ANT1	1560-1620MHZ	INTERFERES WITH THE UAV GPS SATELLITE POSITIONING SIGNAL, CAUSING THE UAV TO BE UNABLE TO LOCATE.
ANT2	2400-2486MHZ	VOC INTELLIGENT SWEEP INTERFERES WITH THE REMOTE CONTROL SIGNAL, CAUSING THE UAV TO BECOME A "BROKEN KITE"
ANT3	5720-5850MHZ	VOC INTELLIGENT SWEEP INTERFERENCE PATTERN TRANSMISSION SIGNAL, FORCING 5.8G FREQUENCY PATTERN TRANSMISSION FAILURE
INDICATE		
DRIVE	ANT2+ANT3	LONG DISTANCE WARNING DRIVE, CLOSE DISTANCE FORCED DRIVE
CRASH LAND	ANT1+ANT2+ANT3	A QUICK VERTICAL CRASH LANDING OR A SHORT SUSPENSION FOLLOWED BY A QUICK VERTICAL CRASH LANDING

# PRODUCT DISPLAY











