

# Handheld Metal Spectrometer

DIX5-700Y/DIX5-900Y



# Handheld Metal Spectrometer Can be measured

#### 01 Alloy Metals

Stainless steel, copper alloy, aluminum alloy, etc.



#### Ogeological Ores

Geological exploration, copper ore, iron ore, bauxite, etc.



#### OB Precious Metals

Gold, platinum, silver, rhodium, RoHS testing, hazardous substances testing for electronic products



#### OA Coating Thickness

Silver-plated copper, zinc-plated iron, archaeology (bronze, porcelain, etc.)



# Environmentally Friendly Heavy Metals

Soil heavy metal detection lead, mercury, cadmium, etc.



# D9X-5 Typical Applications




Rapid investigation and measurement of polluted metal components, pollution patterns, and pollution convenience in polluted water and wastewater




On-site detection of metals involved in RCRA and priority-controlled polluted metals



Provide theoretical basis for analysis of sand, sludge, solid waste, soil, mud, dust, dust filtration, film layer, etc.



Can dispose of harmful substances such as original land, polluted water, wastewater on-site and provide in-depth analysis of pollution control and remediation methods




Provide detection and data support for diseases caused by environmental pollution

# **Application Examples**

# Ore Analysis









### **Identification of Cultural Relics**



Bronze



Obsidian



Porcelain



Murals



il paintings



Glass

# **Element Analysis**












## **Precious metal identification**



Element name	Test results(%)	+/-
Au (Gold)	65.5	0.2
Ag (Silver)	24.430	0.17
Cu (Copper)	10.013	0.085

Spectrum test

# Handheld metal spectrometer Test Interface



## **Product Features**



Two-color warning system Power on green lighta



Test red light flashes Status at a glance



More backlit Clearly visible under strong light





Easy to use One-button operation



No need to prepare samples Can be measured directly



TR" hort" optical path design No need to fill nitrogen, significantly improve lightness

# Technical Parameters

Weight	1.6kg (with battery)
Dimensions	254X79X280MM (LXWXH)
Excitation source	SOKV/200UA upper limit, tube pressure and flow can be freely adjusted AG, AU, W, RH targets (optional)
Detector	High-sensitivity silicon drift detector
Detection range	elements between MG and AM
Display system	industrial-grade resistive touch screen, screen size: 4.3 inches Dedicated operating system and Langsheng analysis software, operating language including Chinese, English and other languages, automatically

environment brightness

adjust the display brightness according to the external

Data processing

built-in 32G storage USB, Bluetooth, WIFI, the device can be connected to the Internet, the instrument can be remotely set and repair data, can be output in EXCEL and PDF format, users can customize to create professional reports

Heat dissipation The instrument is equipped with a dedicated T-slot heat dissipation device to improve the heat dissipation performance of the instrument, without frequently waiting for the detector to cool down

Safety

Built-in DOUBLEBEAMTM technology automatically senses whether there is a sample in front to improve the safety and protection level of the ray, waterproof and dustproof, shockproof suitcase, LAN SCIENTIFIC dedicated safety rope

Power system

Intelligent battery with MSBUS bus, real-time monitoring of battery, remaining capacity of backup battery, battery complies with aviation dangerous goods transportation regulations, single battery can work continuously for about 8 hours



